DATASHEET

20mm Conduit Flexible Halogen free black 1000N Turbo



General data

HFX FLexible Conduit light gauge
Corruguated
Coils of 50 mtr for 16-25mm conduit
Coils of 25 mtr for 32-63mm conduits
In accordance with IEC/EN 61386-22, IEC60423, LSFoH Low smoke - zero Halogen
1000N

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Halogen free	Impact strength	Inner diameter	Material	Operating temperature	Outer diameter
HFXP16 SW	16mm Conduit Flexible Halogen free black 1000N Turbo	black	True	1000 Newton	10 mm	PP Blend	-25 – 105	16 mm
HFXP20 SW	20mm Conduit Flexible Halogen free black 1000N Turbo	black	True	1000 Newton	13.5 mm	PP Blend	-25 – 105	20 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION