

DATASHEET



General data

Monobloc single section 19" cabinets with reduced depth

Ideal for installing patch panels or power supply din rails

Robust welded structure in cold rolled steel

5mm tempered glass door, removable and reversible

A pair of uprights that can be positioned in depth at 3 levels

Constructed from 1.5mm steel plate

Complete with grounding kit and mounting kit

Maximum supported load of 30 Kg; IP20 protection

CE certification according to the EN 62208 standard

Compliance with IEC297; IEC297-1; IEC297-2; IEC297-3; EN61439-1; EN60529; EN12150-1

Compliance with the UNI EN ISO 9001: 2008 standard

Dimensions (LxHxP): 600 x 655 x 300 mm, 12U

Powder coated with RAL 7035 colors (gray)

*** The image is indicative and has the sole purpose of highlighting the structure of the cabinet; for color and size refer to the product sheet**

12-unit flat monobloc single-section 19" wall-mounted cabinet with reduced depth, particularly suitable for installing patch panels or Din rails for power supply

Robust welded structure in cold rolled steel

Door in 5 mm tempered glass, easily removable and reversible, 180° opening angle, lock with key

Blind rear panel

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

Blind side panels

Predisposition for cable entry on the base and on the roof through 6 holes with a diameter of 27 mm and 6 pre-cut rectangular profiles (70 x 30 mm)

A pair of 19" 1.5 mm uprights, adjustable in depth to three levels (maximum useful depth 270 mm with the upright fully advanced)

Slots for air passage in the upper and lower part of the front side

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Max. Load	Number of height units
I-CASE EC-1230G		grey	30 kg	12 U

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

