DATASHEET

Adapter HDMI Male to DVI Female









General data

- 19-pin HDMI Male to DVI-D 24 + 1 dual link female
- Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference
- Provides up to 5 Gbps of bandwidth
- PVC coating cast

Contacts

- Gold Plated
- PVC coated cast
- Shielded

Internal Specifications

- Inner conductor: AWG 30
- 7-wire (50 mm)
- Shielded
- Current rating: 5 A DC
- Voltage: 300 V DC
- Insulation resistance: 50 MOhm
- Resistance of conductors: 2 Ohm
- Plastic coating resistant to temperature

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Adapter HDMI Male to DVI Female

Dimensions
• 40.2 x 64.0 x 15.2 mm (L x W x H)

Certifications
• UL 1007
• ISO9002
• RU
• CE

Package Contents
• 1x HDMI M to DVI-D 24 + 1 F

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour
IADAP-HDMI-606	Adapter HDMI Male to DVI Female	black

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION