

DATASHEET



General data

Docking station with USB-C™ USB 3.2 Gen.1 port and five outputs:

- one USB Type-A port
- one USB-C™ port
- one SDXC card reader port
- one port for a micro SDXC card reader
- one HDMI 4K@30Hz port

Features

The perfect solution, to integrate various devices into a compact workstation

The USB-C™ port has only a data transfer function

USB ports allow the connection of high-speed USB devices such as USB flash or SSD with transfer speeds of up to 5 Gbps

Fast access to photos and other multimedia content via the integrated micro SD/SD/TF card reader

Compatible with SD, SDHC, SDXC, MicroSD, Micro SDHC and Micro SDXC cards

Add an additional HDMI display via the USB-C™ port on any computer or laptop

The four holes on the bottom of the case allow you to attach the docking station to the table with screws

Supports USB3. 2 Gen.1 5Gbps and is backwards compatible with previous standards

Maximum video resolution supports 4K@30Hz

Easy to transport

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.

DATASHEET

Size

Width: 115.43 mm

Depth: 34.64 mm

Height: 16.20 mm

Compatibility

Windows

Mac

Android

Contents of the box

USB hub with SD/micro SD reader and HDMI

User manual

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
IADAP-USBC-935		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.

