

DATASHEET



General data

The IADAP USBC-ETGIGA USB-C™ to Ethernet converter adapter is capable of supporting a network speed of 10/100/1000 Mbps (depends on home network).
It is plug and play, requires no software installation and offers Gigabit Ethernet connectivity.
Take advantage of the speed and reliability of the Internet through RJ45 cable routers.
Compared to WIFI, Internet via USB-C™ to Ethernet Hub Adapter is faster and more stable, thanks to minimal loss.
Ideal for online gaming and latency-free 4K streaming.

Features

- Supports USB-C™ input and RJ45 Ethernet output
- USB bus power supply (no external power supply)

Technical specifications

- USB-C™ input
- RJ45 outgoing network connection
- Operating temperature: 0 ° C ~ 45 ° C
- Operating humidity: 10% ~ 90% RH (non-condensing)
- Storage temperature: -10 ° C ~ 70 ° C
- Storage humidity: 5% ~ 90% RH (non-condensing)
- Bus powered

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

Dimensions

Width: 24.1 mm

Depth: 45.0 mm

Height: 14.0 mm

Package Contents

USB-C™ to RJ45 IADAP USBC-ETGIGA adapter

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
IADAP-USBC-ETGIGA		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

