


DATASHEET



General data

IADAP USBC-HDMI4K is a USB-C™ to HDMI adapter which allows you to transmit signals from your host PC to an HDMI monitor. This adapter enables to output HDMI video with max resolution 4k/30Hz. It can work on all USB-C™ and Thunderbolt™ 3 host that supports DP Alt mode. When working on Thunderbolt™ 3 host, this product transmits DP signal.

Features

Input connector: male USB-C™

USB-C™ supports DP1.2 Alt mode

Output connector: HDMI

Supports:

HDMI max 4K/30Hz

6/8/10/12 bit color depth output

Output pixel format RGB 4:4:4 / YCbCr 4:4:4 / YCbCr 4:2:2

HDCP 2.2 and HDCP 1.4

Technical specifications

Input connector: male USB-C™

Output connector: female HDMI

HDMI resolution: 4Kx2K@30Hz

Operating Temperature: 0°C ~ 45°C

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

Operating Humidity: 10% ~ 85% RH (without condensation)
 Storage Temperature: -10°C ~ 70°C
 Storage Humidity: 5% ~ 90% RH (without condensation)
 Power Source: Bus Power

Dimensions: 40 x 23,1 x 9,6 mm

Certifications: FCC, CE

Package contents
 USB-C™ to HDMI Adapter 4Kx2K@30Hz

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
IADAP-USBC-HDMI4K		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

