


DATASHEET



General data

USB-C™ 3.2 male to HDMI2.1 female adapter
 USB-C™ to HDMI2.1 7680*4320 8K@60Hz, data rate up to 8Gbps
 Gold-plated connectors
 Cable length: 15cm
 Chip set: VMM7100
 Complies with VESA Displayport Alt Mode via USB C Standard 1.0
 Complies with USB 3.0 performance specification
 The output device supports all functions of USB-C™ 3.2/USB 4/Thunderbolt 3/4
 Complies with HDMI2.1, HDMI2.0b, HDMI1.4 and DVI1.0
 Supports HDCP 1.4/2.2/2.3
 Supports 7680*4320@60Hz; 3840*2160@120Hz; 3840*2160@60Hz
 Supports HDR10
 Supports mobile phones, tablets, laptops and desktops with full functionality

Certifications

EC
 WEEE
 REACH
 RoHS

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

Contents of the box

USB-C™ 3. 2 plug to HDMI 2.1 socket adapter

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
IADAP-USBC-HDMI8		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

