

DATASHEET



General data

IADAP USBC-VGAC is a USB-C™ to VGA Adapter. It allows you to transmit signals from a USB-C™ source to a high definition VGA display (TV sets, projectors, etc). It can work on Macbook or Google new Chromebook Pixel and other USB-C supported devices. With this product, you can watch videos or slideshows together on the big screen.

Features

- Supports USB-C™ input, VGA output
- USB-C™ supports reversible plug
- Supports VGA Resolution up to 1920x1200@60Hz
- Plug and play

Technical specifications

- Input connector: male USB-C™
- Output connector: female VGA
- VGA resolution: 1920x1200@60Hz
- Operating Temperature: 0°C ~ 45°C
- Operating Humidity: 10% ~ 85 % RH (no condensation)
- Storage Temperature: -10°C ~ 70°C
- Storage Humidity: 5% ~ 90 % RH (no condensation)
- Power Source Bus Power

This datasheet was created automatically on 12-09-2026 . Technical changes reserved.



DATASHEET

Dimensions: 35 x 26,1 x 13,1 mm

Certifications: FCC, CE

Package contents
USB-C™ to VGA adapter

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
IADAP-USBC-VGAC		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 12-09-2026 . Technical changes reserved.

