


DATASHEET



Clean and Minimalist Design



More Features



Angle Adjustable

Allows smooth adjustment for a better viewing angle.



General data

This Dual Monitor Stand is designed for commercial and retail applications. The mount allows monitors to swivel a full 360° for interaction or information displays, which provides convenient communications access between sales and customers. Each mount features a quick release VESA plate for easy display installation, wiring and maintenance. Pedestal base provides additional stability, fits most installation needs. Monitor height is vertically adjustable for best monitor placement.

Features

- Continuous Swivel: for an optimal viewing angle
- Free-Tilting Design: for multiple monitor viewing angles
- 360° Rotary VESA Plate: for more viewing experience
- Detachable VESA Plate Design: enables easy installation
- Built-in Cable Management: for an organized and neat workspace

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

Technical Specifications

Material: Steel, Aluminum, Plastic
 Surface Finish: Powder Coating
 Color: Matte Black
 Dimensions: 300 x 300 x 446 mm
 Fit Screen Size: 17"-32"
 Fit Curved Monitor
 Weight Capacity: 16 kg (8 kg for each monitor)
 VESA Compatible: 75x75, 100x100
 Tilt Range: +15°~-15°
 Swivel Range: +180°~-180°
 Screen Rotation: +180°~-180°
 Arm Full Extension: 36 mm
 Pole Height: 411 mm
 Installation: Freestanding
 Quick Release VESA Plate
 Cable Management

Package contents

Base of support
 Pole
 2 Brackets
 Fixing accessories (screws, plugs, etc...)
 Installation instructions

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Angle of inclination	Pivoting range
ICA-LCD-402		15 - 15 °	180 - 180 °

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

