

DATASHEET

DVI-D Dual-Link Connecting cable M / M, black, 1.8 m



General data

- Digital signal and dual link: allows to reach high speed digital transmission (Single or Dual Link) at 4.95 Gbps or 9.9 Gbps
- Analog coaxial lines: allows the attainment of high speed for the analog signal up to 2.5 GHz

Features

- Full triple shielding: foil + braid + PiMF for excellent performance EMI / RFI
- Contacts with rough design LFH™: provides two points of contact for optimal signal integrity and reduces insertion force and ensures high reliability
- Supports resolutions up to 2560x1600
- Plug & Play: allows systems to be connected and disconnected without losing configuration or reconfigure devices
- Connector: 2x DVI Digital (DVI-D) 24 + 1 M/M

Package Contents

- 1x Connecting cable with DVI Digital (DVI-D) 24 + 1 M / M

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Length
ICOC-DVI-8105	DVI-D Dual-Link Connecting cable M / M, black, 0.5 m	Black	0.5 m

This datasheet was created automatically on 04-10-2026 . Technical changes reserved.



DATASHEET

DVI-D Dual-Link Connecting cable M / M, black, 1.8 m

ICOC-DVI-8100	DVI-D Dual-Link Connecting cable M / M, black, 1.8 m	Black	1.8 m
ICOC-DVI-8130	DVI-D Dual-Link Connecting cable M / M, black, 3 m	Black	3.0 m
ICOC-DVI-811C	DVI-D Dual-Link Connecting cable M / M, black, 10 m	Black	10.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 04-10-2026 . Technical changes reserved.

