

DATASHEET

HDMI High Speed Mini HDMI M / HDMI M 1,8m



General data

- Mini HDMI 19-pin male to HDMI 19-pin male, with gold-plated connections
- Supports HD resolutions beyond 1080p and Deep Color
- Compliant with HDMI High Speed
- Up to 10.2 Gbps at 340 MHz bandwidth
- Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference

Standards and Certifications

- UL 20276
- ISO9002
- RU
- EC

General Information

- Bandwidth: 10.2 Gbps
- 340 MHz
- Meets or exceeds existing HDMI standards
- Maximum resolution: 4K

Contacts

- 1x HDMI 19-pin male
- 1x Mini HDMI 19-pin male (C)
- Molded PVC

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

HDMI High Speed Mini HDMI M / HDMI M 1,8m

- Shielded, aluminium and braided
- AWG 30

Electrical Information

- Level of current: 0.5 A DC
- Withstanding voltage: 300 V DC
- Insulation resistance: 50 MOhm
- Conductive resistance: 2 Ohm

Package Contents

- Cable High Speed Mini HDMI Male to HDMI Male

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Length
ICOC-HDMI-B-015	HDMI High Speed Mini HDMI M / HDMI M 1,8m	Black	1.8 m
ICOC-HDMI-B-025	HDMI High Speed Mini HDMI M / HDMI M 3m	Black	3.0 m
ICOC-HDMI-B-050	HDMI High Speed Mini HDMI M / HDMI M 5m	Black	5.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

