

# DATASHEET

## HDMI to DVI-D M/M Video Cable, black, 1,8 m



### General data

- HDMI 19-pin male to DVI-D 24 + 1 male with gold contacts
- Allows you to connect a HDMI video source and a DVI-D device
- Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference
- Supports existing HD video formats (720p / 1080i and 1080p / 60), advanced (480p) and standard (NTSC or PAL)
- Moulded PVC

### Standards and Certifications

- Meets or exceeds standard HDMI and DVI-D at the same time
- Compatible with devices DVI-D dual link
- UL
- ISO
- RU
- EC

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



# DATASHEET

## HDMI to DVI-D M/M Video Cable, black, 1,8 m

### Contacts

- 1x HDMI 19-pin male
- 1x DVI-D 24 + 1-pin male
- Shielded
- Inner conductor: AWG 28

### Cable

- Shielded
- Level of current: 0.5 A DC
- Withstanding voltage: 300 V DC
- Insulation resistance: 10 MOhm
- Conductive resistance: 1 Ohm

### Package Contents

- 1x Monitor cable HDMI 19-pin male to DVI-D 24 + 1 male

### Tekniske egenskaber

### Available variants

| ArtNr.          | Bezeichnung                                 | Length |
|-----------------|---------------------------------------------|--------|
| ICOC-HDMI-D-010 | HDMI to DVI-D M/M Video Cable, black, 1 m   | 1.0 m  |
| ICOC-HDMI-D-018 | HDMI to DVI-D M/M Video Cable, black, 1,8 m | 1.8 m  |
| ICOC-HDMI-D-030 | HDMI to DVI-D M/M Video Cable, black, 3 m   | 3.0 m  |
| ICOC-HDMI-D-045 | HDMI to DVI-D M/M Video Cable, black, 5 m   | 5.0 m  |
| ICOC-HDMI-D-100 | HDMI to DVI-D M/M Video Cable, black, 10 m  | 10.0 m |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

