

# DATASHEET



## Durable Materials



## General data

Cable based on a new technology that offers the best data transmission between the HDMI™ source and HDMI™ display. The five twisted pairs offer better data transmission between devices

Triple shielding with resistant connectors for better performance able to optimize the signal with data integrity, even in installation environments subject to the worst EMS interference

ATC certified, this cable fully complies with the requirements of the worldwide HDMI™ standard. All cable materials are 100% RoHS compatible and lead free

Connections from HDMI™ 2.0 19-pin male to HDMI™ 19-pin male

High-speed, bidirectional communication up to 100 Mbps

Supports 4K \* 2K / 60Hz resolution

Compliant with HDMI™ High Speed specifications

Die-cast PVC connector cover

HDMI™ Ethernet Channel: supports internet connection via HDMI™ (HEC)

Audio Return Channel (ARC) : allows an HDMI™ connected to a TV with an integrated tuner to send the audio data "upstream" to a surround sound system, eliminating the need for a separate audio cable

Supports 3D: defines input / output protocols for the main 3D video formats, also for games and 3D home theater applications

## General information

Bandwidth: 18 Gbps

Maximum resolution: 4096 × 2160 60 Hz

This datasheet was created automatically on 26-10-2026 . Technical changes reserved.



# DATASHEET

600 MHz  
Supports HEC

Connectors and cable  
2 x HDMI™ 2.0 19-pin male  
Gold coated contacts  
Die-cast PVC connector covers  
Shielded, braid and aluminum foil  
Internal conductors: AWG 30  
Cable diameter: 6.0 mm

Features  
Supports YCbCr 4: 2: 0  
Supports 32 audio channels  
Supports 1536 kHz audio  
Supports 4 audio streams  
Supports 2 audio streams  
Supports 21: 9 display  
Electrical information  
Current index: 0.5 A DC  
Supports voltage 300 V DC  
Insulation resistance: 50 MOhms  
Conductive resistance: 2 Ohms

Standards and certifications  
UL20276, ISO 9002, CE, RoHS, REACH

## Tekniske egenskaber

### Available variants

| ArtNr.            | Bezeichnung | Colour | Length |
|-------------------|-------------|--------|--------|
| ICOC-HDMI2-4-005T |             | Black  | 0.5 m  |
| ICOC-HDMI2-4-010T |             | Black  | 1.0 m  |
| ICOC-HDMI2-4-020T |             | Black  | 2.0 m  |
| ICOC-HDMI2-4-030T |             | Black  | 3.0 m  |
| ICOC-HDMI2-4-050T |             | Black  | 5.0 m  |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 26-10-2026 . Technical changes reserved.

