

DATASHEET

HDMI High Speed with Ethernet Flat Cable 4K 60Hz 5m



General data

- High Speed HDMI 2.0 flat cable with high quality Ethernet
- Tangle resistant design; allows easy cable management
- Supports HDMI with Ethernet, Audio Return Channel, 3D video, 4K @ 60Hz Display and Deep Color
- Activates the ARC audio transmission of the TV for transmission via the audio system; no additional audio cable is required
- High-speed Ethernet, two-way communication up to 100 Mbps
- Up to 10.2 Gbps of 340 MHz
- Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference
- Compatible with any HDMI device, such as Blu-ray, game consoles, stereo, PC and more

General information

- HDMI 2.0
- Bandwidth: 10.2 Gbps of 340 MHz
- Supports HEC
- Compliant or superior to existing HDMI standards
- Length: 0.5 meters

Connectors

- (2) HDMI 19 pin male

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

HDMI High Speed with Ethernet Flat Cable 4K 60Hz 5m

- Contacts with gold coating
- PVC die-cast connector covers
- Connector for cable clamp

Cable

- 30 AWG cable
- Double shielding
- Current index: 0.5 A DC
- Voltage: 300 V DC
- Insulation resistance: 10 MOhms min.
- Conductive resistance: 5 Ohm
- Thermal plastic casing

Standards and certifications

- UL 20276
- ISO 9001
- HDMI 2.0
- RoHS

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Length
ICOC-HDMI2-FE-005TY	HDMI High Speed with Ethernet Flat Cable 4K 60Hz 0,5m	Black	0.5 m
ICOC-HDMI2-FE-010TY	HDMI High Speed with Ethernet Flat Cable 4K 60Hz 1m	Black	1.0 m
ICOC-HDMI2-FE-020TY	HDMI High Speed with Ethernet Flat Cable 4K 60Hz 2m	Black	2.0 m
ICOC-HDMI2-FE-030TY	HDMI High Speed with Ethernet Flat Cable 4K 60Hz 3m	Black	3.0 m
ICOC-HDMI2-FE-050TY	HDMI High Speed with Ethernet Flat Cable 4K 60Hz 5m	Black	5.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

