DATASHEET









General data

Provides mini-DisplayPort 20-pin male to DisplayPort 20-pin male connections
Provides wide bandwidth, digital audio / video signals from monitors and peripherals equipped with Mini-DisplayPort and DisplayPort - up to 4K @ 60Hz resolution
Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference
Plug and Play for box-to-box applications
Die-cast PVC connector covers
Connectors
mini-DisplayPort 20-pin male
20-pin male DisplayPort

Technical characteristics
Gold-plated contacts
Die-cast PVC
With cable gland
4K @ 60Hz resolution
AWG 32
OD 4.8mm

Package contents
Mini-DisplayPort to DisplayPort monitor cable

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Length
ICOC-MDP-010T4K		white	1.0 m
ICOC-MDP-020T4K		white	2.0 m
ICOC-MDP-030T4K		white	3.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION