DATASHEET







General data

USB Type-C™ male to Type-C™ female
Connects a USB 3.2 Gen 2 SuperSpeed type-C™ device to a SuperSpeed type-C™ port
Supports speeds up to 10 Gbps
Supports USB Power Delivery (PD3) and fast charging up to 100W
SuperSpeed USB for ultra-fast data transfer without any data degradation
Useful for charging USB-C™ devices such as notebooks, Macbook Pro®, smartphones and tablets from a USB-C™ PD wall charger or power bank

Standards and certifications
CE
REACH
RoHS
USB 3.2 Gen 2

Connectors
1x USB-C™ male; 1x USB-C™ female
Gold-plated contacts for long life
Elegant aluminum connector covers

Cable

This datasheet was created automatically on 07-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Double shielded to reduce electromagnetic interference
Supports current up to 5A
Supported power range: 100W

Package Contents
USB 3.2 Gen2 Type-C™ cable

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Length
ICOC-MUSB322-CMF-010		schwarz	1.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION