

DATASHEET

USB 3.0 Cable A/A, 1.0m



General data

- USB 3.0 Type-A male to USB 3.0 Type-A female
- Extends USB cable length
- Supports speed up to 5 Gbps
- SuperSpeed-USB for ultra-fast data transfer without any degradation of the data transmission
- Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference

Standards and Certifications

- UL
- USB 3.0, 2.0, 1.1, 1.0

Connections

- 1x Type-A male
- 1x Type-A female

This datasheet was created automatically on 04-08-2026 . Technical changes reserved.



DATASHEET

USB 3.0 Cable A/A, 1.0m

- Molded PVC
- 28 AWG Connectors

Cable

- Withstanding voltage: 300 V DC 10 ms
- Insulation resistance: 5 MOhm
- Contact resistance: 10 Ohm

Package Contents

- SuperSpeed-USB Extension Cable

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Length
ICOC-U3-AA-005-EX	USB 3.0 Cable A/A, 0.5m	0.5 m
ICOC-U3-AA-10-EX	USB 3.0 Cable A/A, 1.0m	1.0 m
ICOC-U3-AA-20-EX	USB 3.0 Cable A/A, 2.0m	2.0 m
ICOC-U3-AA-30-EX	USB 3.0 Cable A/A, 3.0m	3.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 04-08-2026 . Technical changes reserved.

