


DATASHEET



General data

Point-to-point HDMI extender that allows to obtain a signal transmission without latency.

The 4K @ 60Hz HDMI signal can be extended using a Cat.6 / 6A / 7 network cable. It is equipped with an HDMI port on the local unit, supports IR passthrough, audio output on 3.5mm connection.

It is a reliable and high resolution video transmission solution, ideal for outdoor advertising, video clips, monitoring system, home entertainment, conferences, etc.

Features

- Transmission with zero latency

- Extends the 4K @ 60Hz signal up to 70 meters through Cat. 6 / 6A / 7 network cable

- The receiver supports stereo output on 3.5mm connection

- Supports HDR10

- Supports EDID Passthrough and audio downscaling

- The transmitter supports local HDMI output

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



DATASHEET

Supports IR Passthrough
Lightning protection, surge protection and antistatic protection

Technical specifications

Inputs: T 1xHDMI type A female; R 1xRJ45 female
Outputs: T 1xHDMI type A female; 1xRJ45 female; R 1xHDMI type A female
Maximum data transfer 18Gbps
Maximum transmission bandwidth 600MHz
Pass-through EDID
HDMI 2.0 compatible
HDCP 2.2 compatible
Maximum video resolution 4K @ 60Hz
Maximum transmission distance 70 meters
Audio formats: LPCM / DTS-HD / DTS-Audio / Dolby Digital 5.1CH / Dolby Atmos
3.5mm IR interface
Reception range less than 5m
Infrared frequency: 20KHz-60KHz
Environmental characteristics
Operating temperature: -20 / 60 ° C
Storage temperature: -30 / 70 ° C
Humidity 0 - 90% RH (non-condensing)

Package Contents

1x Transmitter
1x Receiver
2x DC5V / 1A power supply
1x IR blaster extension cable
1x IR receiver extension
4x Mounting Bracket; 10 screws
User Manual

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Number of camera inputs	Number of monitor outputs
IDATA-EXT-565		1	1

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

