DATASHEET









General data

HDMI extender consisting of a USB-C™ transmitter and an HDMI receiver; Achieves zero-latency transmission over CAT.6/6A/7 network cable of UHD video and audio signals
Supports 4K@60Hz Type-C video signal transmission up to 60 meters and 25 meters for 4K@120Hz
Compatible HDMI 2.0, HDCP 2.2, HDCP 1.4; Maximum transmission speed 18Gbps
Audio formats: PCM, DTS, Dolby; HDR10 supported; HDMI 3D supported; EDID Supported, automatic downscaling
Ideal for a variety of applications: education, training, conferences, gaming, home entertainment and more.
TX/RX dimensions: 71.5 (L) x 26.0 (W) x 15.0 (H) mm; ABS material; Black colour

Technical specifications
Voltage
TX: power supply from signal source voltage
RX: DC 5V500mA
Power consumption TX < 3W, RX < 3W
HDMI 2.0
HDCP 2.2, HDCP 1.4
Maximum transmission speed 18 Gbps
Supported resolutions: 1280x720, 1280x960, 1366x768, 1440x900, 1680x1050, 1920x1080, 1920x1200, 720p@50/60Hz, 1080i@50/60Hz, 1080p@24/25/3 0/50/60/ 120Hz, 2560x1440@50/60/ 120/144Hz, 3840x2160@24/25/30/50/60/100/120Hz, 4096x2160@24/25/30/50/60Hz
TMDS signal 0.7~1.2Vp-p (TMDS)

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DDC signal 5Vp-p (TTL)
Transmission distance:
CAT6/6A/7 4K@60Hz≤60m
2560x1440@120/144Hz ≤30m
4K@100/120Hz≤25m
Audio formats: PCM, DTS, Dolby
HDR10 supported
HDMI 3D supported
EDID Supported, automatic downscaling
ESD protection:
- 1st level 2 contact discharge (±4KV)
- 1b Level 3 air discharge (±8KV)
- Implementation of the standard: IEC61000-4-2
TX/RX dimensions: 71.5 (L) x 26.0 (W) x 15.0 (H) mm
TX weight: 17 g; RX: 17.5g
ABS material
Colour: Black
Environmental characteristics
Working temperature -20~55℃
Storage temperature -30~60℃
Humidity 0~90%RH (non-condensing)

Box Contents
USB-C™ Transmitter
HDMI receiver
USB cable
User Manual

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Number of camera inputs	Number of monitor outputs
IDATA-EXT-600HC		1	1

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION