DATASHEET









General data

This HDMI Extender allows you to transmit the HDMI signal over long distances using a Cat. 5E / 6 / 6A / 7 network cable.
Thanks to the use of network cable, it is possible to reach up to 70m of transmission length with 4K video resolution. Includes transmitter and receiver; supports bidirectional IR passback with 20-60KHz frequency. The receiver can be powered by the transmitter (with transmitter connected to the power supply).

Technical specifications
• Zero latency, without loss of compression
• The HDMI signal can be transmitted up to 70m over Cat.6 / 6A / 7 cable; up to 40m on Cat.5E cable
• Supports up to 10 receivers in cascade
• Entrances:
- TX: HDMIx1; DC2.1x1; 3.5mm F x1 (IR)
- RX: DC2.1x1; RJ45x1; 3.5mm F x1 (IR)
• Outings:
- TX: HDMIx1; RJ45x1; 3.5mm F x1 (IR)
- RX: HDMIx1; RJ45x1; Otticox1; 3.5mm F x1 (IR)
• HDMI source control: controllable via IR passback from RX to TX
• The receiver supports S / PDIF output
• Supports Dolby Audio (Dolby Digital Plus; Dolby True-HD; Dolby Digital; Dolby atmos)
• Supports HDR (YUV4: 4: 4), maximum transmission speed 18Gbps

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

• The transmitter supports an HDMI loop-out
• Supports bidirectional IR passback function (20-60KHz)
• The receiver can be powered by the transmitter via a network cable (only on the first receiver)
• Lightning, overvoltage and antistatic protection
• Metal housing, stable and durable
• Supports HDMI 2.0
• Supports HDCP 2.2
• Video resolutions: 480i @ 60Hz, 480p @ 60Hz, 576i @ 50Hz, 576p @ 50Hz, 720p @ 50 / 60Hz, 1080i @ 50 / 60Hz, 1080p @ 50 / 60Hz, 4K × 2K @ 24/25/30 / 60Hz

Size
• Width: 106.36 mm
• Depth: 98.73 mm
• Height: 26.19 mm

Environmental characteristics
• Operating temperature: 0 ~ 50 ℃
• Storage temperature: -10 □ 70 ℃
• Relative humidity: 0 □ 90% (without condensation)

Package contents
• 1x Transmitter
• 1x Receiver
• 1x 5V / 2A power supply
• 1x Blaster extension
• 1x Receiver extension cable
• 1x User manual

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Number of camera inputs	Number of monitor outputs
IDATA-EXT-676		1	1

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION