
DATASHEET











General data

This HDMI Extender allows you the transmission of the HDMI signal with zero latency up to 70 m using a Networking cable Cat.6/6A/7
Thank's to the use of the network cable it's possible to reach up to 70 m of transmission lenght at 4K video resolution.
Includes transmitter and receiver; Supports bi-directional IR passback function with 20-60KHz frequency.

Features:
Uncompressed signal, zero latency, trasmission without loss of signal
HDMI signal can be transmitted up to 70 m with Cat.6/6A/7 cable; up to 40 m su Cat.5E cable
Supports one to one connection
Input:
- TX: HDMIx1; DC2.1x1; 3.5mm F x1 (IR)
- RX: DC2.1x1; RJ45x1; 3.5mm F x1 (IR)
Output:
- TX: HDMIx1; RJ45x1; 3.5mm F x1 (IR)
- RX: HDMIx1; RJ45x1; Optycalx1; 3.5mm F x1 (IR)
HDMI source control: controllabile through IR passback from RX to TX
The receiver supports S/PDIF output
Supports Dolby Audio (Dolby Digital Plus; Dolby True-HD; Dolby Digital; Dolby atmos)
Supports HDR (YUV4:4:4), maximum transmission speed 18Gbps
The ransmitter supports HDMI loop-out

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

Supports bi-directional IR passback function (20-60KHz)
Lightning, overvoltage and antistatic protection
Metal housing, stable and durable
Supports HDMI 2.0
Supports HDCP 2.2
Video resolutions: 480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz, 1080i@50/60Hz, 1080p@50/60Hz, 4K×2K@24/25/30/60Hz

Dimensions:
Width: 106.36 mm
Depth: 98.73 mm
Height: 26.19 mm
Environmental features:
Operating temperature: 0~50℃
Storage Temperature: -10□70℃
Relative humidity: 0□90% (without condensation)

Package contents:
Transmitter
Receiver
2 5V / 2A power supply
Blaster extension
Receiver extension cable
User manual

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Number of camera inputs	Number of monitor outputs
IDATA-EXT-676E		1	1

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION