



# DATASHEET



## General data

The HDMI extender kit converts the HDMI signal into a network signal and transmits data over Cat. 5E and Cat. 6 cables with FullHD 1080p resolution up to 120 m.

It allows you to connect two displays with HDMI output (one local and one remote) for perfect signal transmission in different places over long distances.

IDATA EXTIP-383IR4 transmits the HDMI signal remotely and distributes it to routers or network switches for cascading: in this way it guarantees its use both as a splitter and as an extender.

Support plug and play function, no need driver installation. It also automatically adjusts the specifications for different cable lengths (1-120m) to achieve the best possible video display without any configuration.

The HDMI extender is also able to support the IR transmission function, which allows using the source device's remote control even from a long distance. Supports IR standard 20/60kHz.

Designed and manufactured for the HDMI standard and network transmission protocol, it is compatible with all types of existing or new systems and offers flexible installation and integration.

Due to the high bandwidth consumption, it is advisable to use these devices with IGMP routers or alternatively in dedicated networks or in separate port-based VLANs.

**Not compatible with previous versions**

### Product Specifications

HDMI signal: HDCP compliant

Resolutions: 480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz, 1080i@50/60Hz, 1080p@50/60Hz

Video encoding: H.264

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



# DATASHEET

Audio format supported: PCM Stereo  
 Bandwidth: 18Mbps  
 Supported network cables: UTP/STP Cat5/5e/6  
 Transmission range: Transmission range up to 120 meters in FullHD 1080p via CAT6 cable  
 It supports up to 253 recipients  
 IR Signal: Supports 20-60kHz IR devices  
 Operating temperature: 0°C□60°C

Power  
 5V DC 1A external power supply  
 Consumption (max.) Transmitter: 3.5 W - Receiver: 3 W

Dimensions  
 (x2 pieces):  
 Width: 130mm  
 Depth: 84mm  
 Height: 23.2mm

certifications  
 FCC  
 WEEE

scope of delivery  
 1x extender transmitter  
 1x extender receiver  
 1x IR transmission cable  
 1x IR receiver cable  
 2x 5V 1A power adapter  
 1x Installation Guide

## Tekniske egenskaber

### Available variants

| ArtNr.             | Bezeichnung | Number of camera inputs | Number of monitor outputs |
|--------------------|-------------|-------------------------|---------------------------|
| IDATA-EXTIP-383IR4 |             | 1                       | 1                         |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

