DATASHEET















General data

The HDMI extender HDbitT offers all the benefits of the latest transmission technology - HDbitT, allowing you to extend the HDMI audio / video signal with a resolution of 1080p 60Hz up to 120m using a single network cable. It supports IR signal transmission, to control media playback of the source device from the position where the display is located.

Technical specifications
• Transmitter Kit and IR receiver with HDMI HDbitT
• Transmission protocol: HDbitT
• Supported resolutions: 480i / 60Hz, 480p / 60Hz, 576i / 50Hz, 576p / 50Hz, 720p / 50/60Hz, 1080i / 50/60Hz, 1080p / 50/60Hz
• Network cable: UTP / STP Cat. 5e / 6
• Transmission distance up to 120m, transmission distance for 1080p 60Hz Full HD on a single Cat. 6 cable
• IR Signal: Supports IR devices 20-60KHz

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

• Operating Temperature: 0°C - 60°C
• Power supply DC5V / 1A
• TX consumption: 3.5W;
• RX consumption: 3W

Installation Requirements
• HDMI source device (computer graphics card, DVD, PS3, HD monitoring equipment, etc.)
• HDMI screens as SDTV, projector with HDMI port.
• Network cables: Network cables UTP / STP Cat. 5e / 6 that meet the standard EIA568B
• Transmission length: 80m Cat. 5 / Cat. 5e, 100m / Cat. 6, 120m

Connections
• Point-to-point connection: up to 120 meters transmission distance through single Cat. 6 cable (with a high quality cable can reach up to 150 meters)
• Connection with Router: Using a router / repeater, you can reach unlimited extensions.
• Point-to-Multipoint Connection: Using a router / switch, a transmitter to multiple receivers, you can accomplish the extender and splitter function.
Note: We recommend the use of a gigabit switch (1000Mbps) for the LAN transmission.

Dimensions
• Width: 96.8 mm
• Depth: 94 mm
• Height: 23.7 mm

Certifications
• EC
• FCC
• RoHS
• WEEE

Package Contents
• 1x HDMI EXTENDER Transmitter TX
• 1x HDMI EXTENDER Receiver RX
• 2x Power Supply DC5V / 1A
• 1x extension cable IR Blaster
• 1x IR receiver extension cable
• 1x Instruction Manual

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Number of monitor outputs	
IDATA-EXTIP-383RV4		1	
IDATA-EXTIP-383V4		1	1

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION