

DATASHEET



General data

- 5 Gigabit Ethernet ports
- 1000Mbps full duplex, 10/100Mbps full/half duplex, auto-negotiation, auto-MDI/MDIX
- Supports 2K MAC address auto-learning and auto-aging
- 9K jumbo frames to increase data transfer rates
- IP multicast filtering through IGMP Snooping V1/V2
- 802.1Q Tag-based VLAN enables network segmentation to improve performance and security
- IEEE 802.1p QoS with 4 priority queues
- Supports storm control for unknown unicast/broadcast/multicast
- Minimizes carbon footprint with energy efficient technology (IEEE 802.3az)
- Operating temperature range from -40°C to 75°C
- 4KV surge protection, 6KV contact/8KV air ESD protection
- Supports DIN rail installation
- Web-based Smart Lite real-time management
- Supports LevelOne IP Locator for easier IP management.

The LevelOne IGS-2105 Hilbert 5-Port Industrial Gigabit Smart Lite Switch is a new generation Ethernet switch, The IGS-2105 offers 5 (10M/100M/1G) RJ45. to enable high-speed networks in mission-critical environments. With industrial standard DIN rail mounting and highly visible status LEDs, the switch provides easy monitoring of port connections. With the new LevelOne IP Locator, the simple switch discovery software, all Hilbert series switches can be searched and information about the switch and IP configuration can be displayed. It is compatible with the most common

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.



DATASHEET

Windows and Mac operating systems.

The LevelOne IGS-2105 offers high hardware performance and environmental flexibility for businesses. The IGS-2105 is ideal for easy management, optimal usability and lower total cost of ownership.

General

Color: Black

Features L2 switching features

- IGMP snooping
- Link Aggregation (Supports static link aggregation)
- Port mirroring
- Cable Test

VLAN

- Supports up to 32 VLANs (out of 4K VLAN IDs)
- MTU/Port/802.1Q VLAN

Quality of Service (QoS)

- Support Port-based/802.1p/DSCP priority
- Support 4 priority queues
- Rate Limit
- Storm control

Administration

- Web-based Graphic User Interface (GUI)
- Supports LevelOne IP Locator for easier IP management.

Miscellaneous

Data rate Gigabit Ethernet

PoE Supported No

Fanless Yes

Manageable Yes

Series HILBERT series

Grade industrial

Others

Approvals and Compliance

- CE
- UKCA
- FCC Part 15, Subpart B Class B
- RoHS

Operating humidity 10% RH ~ 90% RH

Operating temperature -40°C ~ 75°C

Storage humidity 5% RH ~ 95% RH

Storage temperature -40°C ~ 85°C

scope of delivery

- IGS-2105
- Power Terminal Block
- Din rail mount kit

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.



DATASHEET

- Quick Installation Guide
 - Declaration of Conformity
- performance
Switching capacity 10 Gbps

Physical Specifications

Dimensions (W x D x H) 136 x 108 x 38.5 mm

Product weight (kg) 0.35 kg

System specifications

Acoustic noise (dB) 0 dB (A)

Micro switch LOOP, VLAN ON/OFF

Flash memory size 2 MB

Packet forwarding rate 7.44 Mpps

Heat dissipation 17.06 (Btu/H)

Indicator Power, Link/Act

Jumbo frames (KB) 9 KB

MAC address table 2 K

Fastening DIN rail mount

MTBF 43,800 hrs

Packet buffer 1.5 Mbits

Port Configuration 4x 10/100/1000 Mbps RJ-45 copper downlink ports, 1x 10/100/1000 Mbps RJ-45 copper uplink ports

Energy consumption 5 W

Input voltage redundant dual DC 12V/24V/48V

Power supply VDC 12~57V

Standards ● IEEE 802.3 10-BASE-T (Ethernet)

● IEEE 802.3u 100-BASE-TX (Fast Ethernet)

● IEEE 802.3ab 1000BASE-T (Gigabit Ethernet)

● IEEE 802.3x Flow Control (full-duplex flow control)

● IEEE 802.3az: Energy Efficient Ethernet

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
IGS-2105		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.

