

DATASHEET



General data

Completely equipped INFRALAN® splice box with adapter and through-dyed pigtails

The LC Pigtails are stripped off and inserted into the splice cassette

Measurement protocols of LC Pigtails are stored in the box

Metal housing depth adjustable (45mm) via 19" mounting bracket

All versions of the splice box are supplied with 24 coupling openings and fitted with blind inserts if the number of used ports is reduced.

Rear cable entry with 2x M20 openings on each side. The M20 openings can also be made laterally by replacing the opening plate with an angle plate (SB-A-GR-WINKEL). In addition, there is a central cable entry for 20x Simplex cables (up to 4.3mm).

incl. 1 x PG16

6 x self-adhesive fiber guides

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Pigtail	Type of connector external	With number of couplings/adapters
ISB-LCDU-06-3-GR-ABA		grey	12 x LC	LC-Duplex	6
ISB-LCDU-06-3-SW-ABA		Black	12 x LC	LC-Duplex	6
ISB-LCDU-24-3-GR-ABA		grey	48 x LC	LC-Duplex	24

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.



DATASHEET

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

