DATASHEET







General data

USB car charger for smartphones and portable devices, equipped with one USB-A and one USB-C™ port
Allows you to conveniently charge 2 peripherals in the car via the USB connection
Supports Fast Charge technology, capable of charging compatible devices 4 times faster than standard chargers
Power socket: cigarette lighter
Lightweight, ultra-compact charger
Constructed from sleek looking zinc alloy and high temperature resistant

Technical specifications
Input: DC12.0-24.0V
Output 1: DC 5V 3A / 9V 2A / 12V 1.5A (USB-A 18W)
Output 2: DC 5V 2.4A / 9V 2.22A / 12V 1.67A (USB-C™ PD 20W)
Total 38W

Protections
Overcurrent
Overvoltage
Overload
Overheating
Short circuit protection
Low voltage protection

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

Dimensions
Height: 45.8 mm
Diameter: 26.6 mm

Certifications
EC
RoHS

Package Contents
Mini USB-A and USB-C™ car charger

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Model	Number of buses/couplings
IUSB2-CAR5-AC38W		USB charger	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION