

DATASHEET



General data

USB car charger for smartphones and portable devices, equipped with one USB-A and one USB-C™ port
 Allows you to conveniently charge 2 peripherals in the car via the USB connection
 Supports Fast Charge technology, capable of charging compatible devices 4 times faster than standard chargers
 Power socket: cigarette lighter
 Lightweight, ultra-compact charger
 Constructed from sleek looking zinc alloy and high temperature resistant

Technical specifications

Input: DC12.0-24.0V

Output 1: DC 5V 3A / 9V 2A / 12V 1.5A (USB-A 18W)

Output 2: DC 5V 2.4A / 9V 2.22A / 12V 1.67A (USB-C™ PD 20W)

Total 38W

Protections

Overcurrent

Overvoltage

Overload

Overheating

Short circuit protection

Low voltage protection

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

Dimensions

Height: 45.8 mm

Diameter: 26.6 mm

Certifications

EC

RoHS

Package Contents

Mini USB-A and USB-C™ car charger

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Model	Number of buses/couplings
IUSB2-CAR5-AC38W		USB charger	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

