


DATASHEET



General data

6 ADDITIONAL PORTS: Docking station that turns one USB-C™ port into 6 ports, with 4K HDMI port, Gigabit Ethernet and 3 Super High Speed USB 3.0 ports and PD fast charging port

ULTRA HD: The HDMI port streams 4K video directly to your TV, monitor or projector. Thanks to a simple laptop docking station it is possible to obtain very high quality visual effects

5Gbps SUPER SPEED: With data transfer speeds of up to 5Gbps, this USB3.0 hub transmits data 10 times faster than USB 2.0. It allows you to transfer an HD movie in seconds. It is also backwards compatible with USB 2.0 devices

PLUG & PLAY: Compatible with Windows and Mac OS X, no driver installation required. By simply inserting it into your device's USB-C™ port, you can enjoy the extra USB ports

COMPACT AND PORTABLE: Sturdy metal housing with an essential design. Thanks to its small size (105.00 x 39.00 x 12.08 mm) it is very compact and practical to carry around; Supplied with 150mm USB-C™ cable

Hub with 15cm USB cable

Aluminum alloy housing

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.

DATASHEET

Plug and play
Compatibility
Windows 10 and above
Mac OS X v10.10 and above

Size
Width: 105.00 mm
Depth: 39.00 mm
Height: 12.08mm
Cable: 150mm
Environmental characteristics
Operating temperature: 0-50°C
Storage temperature: -40 / +85 °C
Operating Humidity: 0-85%
Storage Humidity: 0-85%

Certifications
EC
RoHS
WEEE

Box Contents
Docking station
User Manual

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour
IUSB32C-HUB6HPDI		grey

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.

