

DATASHEET



General data

Juniper JNP-SFP-25G-LR compatible 25GBASE-LR SFP28 transceiver with LC duplex connection according to MSA standards from the BlueOptics brand. The Juniper JNP-SFP-25G-LR compatible 25GBASE-LR LC Duplex SFP28 has a receiving function (receiver with 1310nm) and a transmitting function (transmitter with 1310nm) for the transmission of optical signals via single-mode fiber optic, taking into account the respective transmission protocol. This Juniper JNP-SFP-25G-LR compatible 25GBASE-LR LC Duplex SFP28 is suitable for use in all common hardware platforms (such as switches, routers, storage systems, load balancers, measuring devices, etc.) that also support the original Juniper JNP -SFP-25G-LR 25GBASE-LR LC Duplex SFP28 official support. Each Juniper JNP-SFP-25G-LR compatible 25GBASE-LR LC Duplex SFP28 supports Ethernet, Fiber Channel over Ethernet or SDH/SONET high-speed applications of up to 25G per second.

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
JNP-SFP-25G-LR-BO		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

