DATASHEET

RJ45 Patch Cord Cat.5e SF/UTP LSZHDraka UC300 TM11 crossed red 5m



General data

RJ45 patch cable Cat.5e SF/UTP LSZH Draka UC300 TM11 crossed

The Cat.5e patch cable has gold-plated contacts and meets the requirements for 2.5Gbit Ethernet.

Technical product properties
• Cat .5e
• SF/UTP cable with AWG26/7
• Jacket material made of halogen-free LSZH
• Fire protection: flame-retardant, halogen-free, low smoke
• Plug connection: RJ45 to RJ45
• Has gold-plated contacts< br>
The jacket of the shielded patch cable is made of halogen-free LSZH material. In addition, the cable offers the option of power supply via PoE according to IEEE802.3af, PoE+ according to IEEE802.3at and 4PPoE according to IEEE802.3bt.

The assignment of the TM11 plugs is the classic crossover for Gigabit Ethernet: 1-3 , 2-6, 3-1, 4-7, 5-8, 6-2, 7-4, 8-5.

The network cable has a copper conductor material and is ideal for applications in structured building cabling,

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Patch Cord Cat.5e SF/UTP LSZHDraka UC300 TM11 crossed red 5m

Industrial Ethernet and in data centers. The bandwidth is up to 100 MHz.

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Length	POE class	Length tolerance
K2793.0,50	RJ45 Patch Cord Cat.5e SF/UTP LSZHDraka UC300 TM11 crossed red 0,5m	0.5 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K2793.1	RJ45 Patch Cord Cat.5e SF/UTP LSZHDraka UC300 TM11 crossed red 1m	1.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K2793.1,5	RJ45 Patch Cord Cat.5e SF/UTP LSZHDraka UC300 TM11 crossed red 1,5m	1.5 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K2793.2	RJ45 Patch Cord Cat.5e SF/UTP LSZHDraka UC300 TM11 crossed red 2m	2.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K2793.3	RJ45 Patch Cord Cat.5e SF/UTP LSZHDraka UC300 TM11 crossed red 3m	3.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K2793.5	RJ45 Patch Cord Cat.5e SF/UTP LSZHDraka UC300 TM11 crossed red 5m	5.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %
K2793.10	RJ45 Patch Cord Cat.5e SF/UTP LSZHDraka UC300 TM11 crossed red 10m	10.0 m	PoE acc. to IEEE802.3af;PoE+ acc. to IEEE802.3at;4PPoE acc. to IEEE802.3bt	±5 %

datasheets.content.drawings

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET


RJ45 Patch Cord Cat.5e SF/UTP LSZHDraka UC300 TM11 crossed red 5m

Belegung Gigabit Crossover:

1	ws/or	3
2	or	6
3	ws/gn	1
4	bl	7
5	ws/bl	8
6	gn	2
7	ws/br	4
8	br	5

-Schirm beidseitig auf Gehäuse!

Gigabit Crossover Pinning zur Direktverbindung von 2 NICs.
(Bei Switch to Switch oder Switch to NIC nicht zwingend)
Empfohlene Leitung: FTP/SFTP ab CAT5e
Steckverbinder: TM11 oder Stewart CAT5e



This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

RJ45 Patch Cord Cat.5e SF/UTP LSZHDraka UC300 TM11 crossed red 5m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION