DATASHEET

Earthing Bar for Network Cabinets 42U, Vertical, incl. 12 x Busbar Clamp







General data

For vertical installation in 42U network cabinets Classic/PRO
Mounting via supporting insulators on the sidely round holes of the 19“ profiles (PRO: please use rear lateral raster holes)
Mountable also in combination with vertically blind panels
For mounting in server cabinets the installation of an additional 19“ profile is recommended
Scope of delivery: copper earthing bar 1800 x 15 x 5 mm, 12 x busbar terminal 1.5 .. 16 mm², 4 x supporting insulator, 8 x thread bolt M6 x 25, 8 x washer, 8 x nut M6, self-locking

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Mounting method
K3930V42	Earthing Bar for Network Cabinets 42U, Vertical, incl. 12 x Busbar Clamp	Screwing

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product’s suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 30-10-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION