

DATASHEET

USB2.0 Connection Cable A-B, M-M, 3.0m, grey, Classic



Classic



General data

Supports data transmission rates up to 480 Mbit/s. Wire construction: AWG28 / AWG24. Shielded: folie + braiding. Plug moulded.

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Length	Diameter	AWG
K5255.0,5	USB2.0 Connection Cable A-B, M-M, 0.5m, grey, Classic	grey	0.5 m	-	-
K5255.1	USB2.0 Connection Cable A-B, M-M, 1.0m, grey, Classic	grey	1.0 m	-	-
K5255.1,5	USB2.0 Connection Cable A-B, M-M, 1.5m, grey, Classic	grey	1.5 m	4.5 mm	24+28AWG
K5255.1,8	USB2.0 Connection Cable A-B, M-M, 1.8m, grey, Classic	grey	1.8 m	-	-
K5255.3	USB2.0 Connection Cable A-B, M-M, 3.0m, grey, Classic	grey	3.0 m	4.5 mm	24+28AWG
K5255.5	USB2.0 Connection Cable A-B, M-M, 5.0m, grey, Classic	grey	5.0 m	-	-
K5255SW.0,5	USB2.0 Connection Cable A-B, M-M, 0.5m, black, Classic	black	0.5 m	4.5 mm	24+28AWG
K5255SW.1	USB2.0 Connection Cable A-B, M-M, 1.0m, black, Classic	black	1.0 m	4.5 mm	24+28AWG
K5255SW.1,8	USB2.0 Connection Cable A-B, M-M, 1.8m, black, Classic	black	1.8 m	-	-
K5255SW.3	USB2.0 Connection Cable A-B, M-M, 3.0m, black, Classic	black	3.0 m	-	-
K5255SW.5	USB2.0 Connection Cable A-B, M-M, 5.0m, black, Classic	black	5.0 m	4.5 mm	24+28AWG

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.




DATASHEET

USB2.0 Connection Cable A-B, M-M, 3.0m, grey, Classic

K5255SW.1,5 | USB2.0 Connection Cable A-B, M-M, 1.5m, black, Classic | black | 1.5 m

datasheets.content.drawings



NOTE:

1. Electrical test:

- (1). 100% open short & miss wire test;
- (2). Insulation resistance: DC 200V 10 MΩ MIN;
- (3). Connect resistance: 3 Ω MAX;
- (4). Temperature range: -20°C to +60°C;

2. RoHS compliant

3. PRINT WORD: USB2.0 HIGH SPEED CABLE 28AWG×1P 24AWG×2C

www.efb-elektronik.de CE

MATERIAL LIST:

④	CONNECTOR	USB B TYPE MALE, NICKEL PLATED SHELL, 1U" GOLD PLATED PIN, WHITE INSULATOR	1 Set
③	CABLE	28AWG CU*1P+24AWG CU*2C+AL+B(COVERAGE RATE IN 65%) USB2.0 HIGHSPEED CABLE JACKET:PVC OD: 4.5 ± 0.2mm	1
②	OVER MOLD	PVC	2
①	CONNECTOR	USB A TYPE MALE, NICKEL PLATED SHELL, 1U" GOLD PLATED PIN, WHITE INSULATOR	1 Set
NO.	MAT. NAME	SPECIFICATION STANDARD	QT' Y

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.