

DATASHEET

DVI Monitor cable Dual Link, DVI-Digital 24+1, AWG28, 2m



General data

Shielding: foil + braiding

Conductor: bare copper, Jacket: PVC

Tinned plugs and gold plated contacts, **housing with full-metal shielding and moulded, for ideal shielding characteristics in rough industrial environment.**

Both sides assembled with ferrite core to dejam signals in the cable (for better EMC characteristics)

Dual link cable

Support for resolution up to 2560 x 1600

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Length	Diameter	AWG
K5434IND.2	DVI Monitor cable Dual Link, DVI-Digital 24+1, AWG28, 2m	black	2.0 m	8.6 mm	28AWG
K5434IND.3	DVI Monitor cable Dual Link, DVI-Digital 24+1, AWG28, 3m	black	3.0 m	8.6 mm	28AWG
K5434IND.5	DVI Monitor cable Dual Link, DVI-Digital 24+1, AWG28, 5m	black	5.0 m	8.6 mm	28AWG

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

DVI Monitor cable Dual Link, DVI-Digital 24+1, AWG28, 2m

regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

