DATASHEET





General data

The new generation of HDMI-Cable with a bandwith of up to 48Gbit.
Supports Features as Dynamic HDR, Dolby Vision und eARC. Also compatible to older HDMI standards.

Supports Ultra High Speed HDMI Video up to 8k 60Hz eg. 4K 120Hz Auflösung
Dynamic HDR, HDCP2.2, 3D, Ethernet Channel, eARC
Tripple shielding: Foil + Braid + PIMF
Conductor material: Bare copper, Jacket: PVC
Gold plated HDMI™ plugs and contacts
Housing shielded and moulded

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Length
K5440SW.1		black	1.0 m
K5440SW.2		black	2.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION