
DATASHEET

RJ45 Patch Cord Cat.5e SF/UTP PVCred boot CCA crossed grey 10m



General data

RJ45 patch cable Cat.5e SF/UTP LSZH Draka UC300 TM11 crossed

The Cat.5e patch cable has gold-plated contacts and meets the requirements for 2.5Gbit Ethernet.

Technical product properties< br>• Cat .5e
• SF/UTP cable with AWG26/7
• Jacket material made of halogen-free LSZH
• Fire protection: flame-retardant, halogen-free, low smoke
• Plug connection: RJ45 to RJ45
• Has gold-plated contacts< br>
The jacket of the shielded patch cable is made of halogen-free LSZH material. In addition, the cable offers the option of power supply via PoE according to IEEE802.3af, PoE+ according to IEEE802.3at and 4PPoE according to IEEE802.3bt.

The assignment of the TM11 plugs is the classic crossover for Gigabit Ethernet: 1-3 , 2-6, 3-1, 4-7, 5-8, 6-2, 7-4, 8-5.

The network cable has a copper conductor material and is ideal for applications in structured building cabling, Industrial Ethernet and in data centers. The bandwidth is up to 100 MHz.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Patch Cord Cat.5e SF/UTP PVCred boot CCA crossed grey 10m

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Length	POE class	Length tolerance
K5450.0,5	RJ45 Patch Cord Cat.5e SF/UTP PVCred boot CCA crossed grey 0,5m	0.5 m	No	±5 %
K5450.1	RJ45 Patch Cord Cat.5e SF/UTP PVCred boot CCA crossed grey 1m	1.0 m	No	±5 %
K5450.2	RJ45 Patch Cord Cat.5e SF/UTP PVCred boot CCA crossed grey 2m	2.0 m	No	±5 %
K5450.3	RJ45 Patch Cord Cat.5e SF/UTP PVCred boot CCA crossed grey 3m	3.0 m	No	±5 %
K5450.5	RJ45 Patch Cord Cat.5e SF/UTP PVCred boot CCA crossed grey 5m	5.0 m	No	±5 %
K5450.10	RJ45 Patch Cord Cat.5e SF/UTP PVCred boot CCA crossed grey 10m	10.0 m	No	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION