# DATASHEET





## General data

According to DisplayPort1.4 standard
Resolution up to 8K Ultra HD (7680 x 4320 @ 60Hz)
Conform to HDCP2.2
DisplayPort plugs and contacts gold plated
Tripple shielding
Conductor: bare copper, Jacket: PVC
Pin 20: DP_PWR not connected
**Housing with 360° shielding, moulded and DP lock**

## Tekniske egenskaber

## Available variants

| ArtNr. | Bezeichnung | Colour | Length |
|---|---|---|---|
| K5567SW.1 | | black | 1.0 m |
| K5567SW.2 | | black | 2.0 m |
| K5567SW.3 | | black | 3.0 m |
| K5567SW.5 | | black | 5.0 m |

**Note on Intended Use**

**This datasheet was created automatically on 02-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

**This datasheet was created automatically on 02-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION