


DATASHEET

RJ45 Patch Cord Cat.5e U/UTP LSZH CCA AWG24/7 red 20m

1Gbit Cat.5E



General data

Cable description:

U/UTP Cat.5e AWG24/7 stranded 4 pairs cable
Jacket: LSZH, low smoke & Halogenfree
OD: 5,4mm

RJ45 Connector:

2 x Cat.5e RJ45 plugs 1:1 IEC60603-7
Moulded strain relief with bend and latch protection
3um gold plated contacts

Application:

ISO IEC 11801, EIA/TIA 568

Printing, Cable:

Cat.5e UTP Patch cable AWG24/7 LSZH

Printing, Polybag label:

Neutral polybag with label printet:
Cat.5e UTP Patch Cable AWG 24/7 LSZH Art. No. and EAN number + barcode

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.5e U/UTP LSZH CCA AWG24/7 red 20m

Printing, Carton box label and Standard neutral carton box:


Cat.5e UTP Patch Cable AWG 24/7 LSZH + Color Art. No. and EAN number + barcode

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Length	Length tolerance
K8110RT.10	RJ45 Patch Cord Cat.5e U/UTP LSZH CCA AWG24/7 red 10m	10.0 m	±5 %
K8110RT.15	RJ45 Patch Cord Cat.5e U/UTP LSZH CCA AWG24/7 red 15m	15.0 m	±5 %
K8110RT.2	RJ45 Patch Cord Cat.5e U/UTP LSZH CCA AWG24/7 red 2m	2.0 m	±5 %
K8110RT.20	RJ45 Patch Cord Cat.5e U/UTP LSZH CCA AWG24/7 red 20m	20.0 m	±5 %
K8110RT.30	RJ45 Patch Cord Cat.5e U/UTP LSZH CCA AWG24/7 red 30m	30.0 m	±5 %
K8110RT.5	RJ45 Patch Cord Cat.5e U/UTP LSZH CCA AWG24/7 red 5m	5.0 m	±5 %
K8110RT.7,5	RJ45 Patch Cord Cat.5e U/UTP LSZH CCA AWG24/7 red 7,5m	7.5 m	±5 %


datasheets.content.drawings



This datasheet was created automatically on 22-09-2026 . Technical changes reserved.

DATASHEET

RJ45 Patch Cord Cat.5e U/UTP LSZH CCA AWG24/7 red 20m



Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.