DATASHEET

32mm rigid plastic pipe HFIRM OP LSF0H grey 320N 3m



General data

HFIRMrigid conduit medium gauge, with molded-on coupler and sectional corrugation.
As standard color Light grey (RAL7035)
Standard lenght 3 meter
In accordance with IEC/EN 61386-21, IEC60423, LSFoH
Mechanical strenght = 320 N
Without Turbo Function

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Fire retardant version	Halogen free	Inner diameter	Material	Operating temperature	Outer diameter
L120066	25mm rigid plastic pipe HFIRM OP LSF0H grey 320N 3m	grey	True	True	21 mm	PP Blend	-25 – 105	25 mm
L120067	32mm rigid plastic pipe HFIRM OP LSF0H grey 320N 3m	grey	True	True	28 mm	PP Blend	-25 – 105	32 mm
L120068	40mm rigid plastic pipe HFIRM OP LSF0H grey 320N 3m	grey	True	True	35 mm	PP Blend	-25 – 105	40 mm
L120069	50mm rigid plastic pipe HFIRM OP LSF0H grey 320N 3m	grey	True	True	45 mm	PP Blend	-25 – 105	50 mm

Note on Intended Use

This datasheet was created automatically on 26-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

32mm rigid plastic pipe HFIRM OP LSF0H grey 320N 3m

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 26-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION