

DATASHEET



General data

NVIDIA MMA2P00-AS compatible 25GBASE-SR SFP28 transceiver with LC duplex connection according to MSA standards from the BlueOptics brand. The NVIDIA MMA2P00-AS compatible 25GBASE-SR LC Duplex SFP28 has a receiving function (receiver with 850nm) and a transmitting function (transmitter with 850nm) for the transmission of optical signals via multimode fiber, taking the respective transmission protocol into account. This NVIDIA MMA2P00-AS compatible 25GBASE-SR LC Duplex SFP28 is suitable for use in all common hardware platforms (such as switches, routers, storage systems, load balancers, measuring devices, etc.) that also support the original NVIDIA MMA2P00-AS 25GBASE- Officially support SR LC Duplex SFP28. Each NVIDIA MMA2P00-AS compatible 25GBASE-SR LC Duplex SFP28 supports Ethernet, Fiber Channel over Ethernet or SDH/SONET high-speed applications of up to 25G per second.

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
MMA2P00-AS-BO		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

