


DATASHEET

MTP®/APC(F)-LC Trunk cable OS2 8 fibers Typ B LSZH yellow 10m

100 Gbit



General data

Application: Suitable for transmission links up to **100 Gigabit**

Construction: 1 multi-connector MTP® on one side,
4 LC-Duplex connector on the other side

LowLoss version: attenuation per Fanout max. 0,35dB

Matrix: 8 fibers

Assignment MTP 1-4 + 9-12

Furcation length: 50cm

Cable diameter multi-connector: 3mm

Cable diameter single-connector: 2mm

Colour: OM4 and OS2 acc. to colour code DIN VDE 0888

MTP Singlemode connectors are in APC version

Tekniske egenskaber

Available variants

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.




DATASHEET

MTP®/APC(F)-LC Trunk cable OS2 8 fibers Typ B LSZH yellow 10m

ArtNr.	Bezeichnung	Halogen free (according to EN 60754-1/2)	Length	Number of connectors connection 1	Number of connectors connection 2	Number of fibres
MTPF08LCOS2-3	MTP®/APC(F)-LC Trunk cable OS2 8 fibers Typ B LSZH yellow 3m	True	3.0 m	1 x MTP®/APC(F)	8 x LC	8
MTPF08LCOS2-10	MTP®/APC(F)-LC Trunk cable OS2 8 fibers Typ B LSZH yellow 10m	True	10.0 m	1 x MTP®/APC(F)	8 x LC	8

datasheets.content.drawings



This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

DATASHEET

MTP®/APC(F)-LC Trunk cable OS2 8 fibers Typ B LSZH yellow 10m



Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.