


DATASHEET

MTP®/APC(F)-MTP®/APC(F) Patch cable OS2 12 fibers Typ A LSZH yellow 7,5m

100 Gbit



General data

Application: Server to Server- / Switch to Switch connection,

Suitable for transmission links up to **100 Gigabit**

Connector manufacturer: **US Conec**

Matrix: 12 Fibers

Singlemode variant always as APC version

Colour: OM5 lime green, OM4 erica-violet, OM3 aqua and OS2 yellow

Available lengths: 1m up to 100m

Note: In each MTP® transmission link, a type B (crossed) patch cable is required

MTP Singlemode connectors are in APC version

Tekniske egenskaber

Available variants

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.




DATASHEET

MTP®/APC(F)-MTP®/APC(F) Patch cable OS2 12 fibers Typ A LSZH yellow 7,5m

ArtNr.	Bezeichnung	Halogen free (according to EN 60754-1/2)	Length	Number of connectors connection 1	Number of connectors connection 2	Number of fibres
MTPF12MTPFOS2-1-A	MTP®/APC(F)-MTP®/APC(F) Patch cable OS2 12 fibers Typ A LSZH yellow 1m	True	1.0 m	1 x MTP®/APC(F)	1 x MTP®/APC(F)	12
MTPF12MTPFOS2-7,5-A	MTP®/APC(F)-MTP®/APC(F) Patch cable OS2 12 fibers Typ A LSZH yellow 7,5m	True	7.5 m	1 x MTP®/APC(F)	1 x MTP®/APC(F)	12
MTPF12MTPFOS2-10-A	MTP®/APC(F)-MTP®/APC(F) Patch cable OS2 12 fibers Typ A LSZH yellow 10m	True	10.0 m	1 x MTP®/APC(F)	1 x MTP®/APC(F)	12
MTPF12MTPFOS2-15-A	MTP®/APC(F)-MTP®/APC(F) Patch cable OS2 12 fibers Typ A LSZH yellow 15m	True	15.0 m	1 x MTP®/APC(F)	1 x MTP®/APC(F)	12

datasheets.content.drawings



This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

DATASHEET

MTP®/APC(F)-MTP®/APC(F) Patch cable OS2 12 fibers Typ A LSZH yellow 7,5m



Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.