

DATASHEET

DIN Rail Power Supply 48V, 480W, 10A, Mean Well



General data

Power supply unit for Din Rail installation for operating e.g. Industrial switching

Metal housing

1Ø, full range input

Compact size, 32 ~ 85,5 mm width

EMV EN55022 Class B

Mount on industrial rails TS-35 / 7.5 or 15

3 year warranty

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Max. output current 1	Power output
NDR-75-48	DIN Rail Power Supply 48V,1.6A, 75W, Mean Well	1.6 A	75 W
NDR-120-48	DIN Rail Power Supply 48V,2.5A, 120W, Mean Well	2.5 A	120 W
NDR-240-48	DIN Rail Power Supply 48V, 5.0A, 240W, Mean Well	5.0 A	240 W
NDR-480-48	DIN Rail Power Supply 48V, 480W, 10A, Mean Well	10.0 A	480 W
POW-4841		2.5 A	120 W

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 27-09-2026 . Technical changes reserved.

