


DATASHEET



General data

The 1.2 mm Duplex Jumper are characterized due to the small outer diameter. This is an advantage for the installers when they have limited space for cable management. The small outer diameter is also useful in projects with high density areas.

Characteristics

Space-saving installation due to the small outer diameter

Halogen free and flame retardant according to IEC-60754-2, IEC-60332-1 and IEC-61034

Connector in colour of category (OM4 is erica-violet)

LC connector in Compact design

EFB fiber connectors meet the quality class Grade B/2 for multimode according to IEC-61753-122-2 (Draft)

pre-coded

100% tested and with individuell measuring protocol

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Length
00323.0,5-1.2		0.5 m
00323.1-1.2		1.0 m

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.



DATASHEET

00323.10-1.2		10.0 m
00323.2-1.2		2.0 m
00323.3-1.2		3.0 m
00323.5-1.2		5.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.

