


# DATASHEET

## Duplex Patchcable LC/APC-LC/APC OS2 G652D 20m LSZH 2mm yellow



### General data

Fiber jumper are well defined components in international standard of structured cabling ISO/IEC11801. Due to many different network protocols created in the last 25 years , also a wide range of connectors had been developed. Some of them are still important today: LC, SC, E2000®, MPO/MTP.

Fiber jumper (patchcord) are defined as shortest connection between passive interface and active deviceport, regarding structured cabling standard. Rating of performance, known as category, as well as performance of total transmission channel, known as link class, Similar descriptions for patchcords: Connection cable, drop cable, adapter cable, interconnecting cord, Jumper

### Features of EFB fiber optic patch cables

Tension relief reinforced with aramid yarn

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

# DATASHEET

## Duplex Patchcable LC/APC-LC/APC OS2 G652D 20m LSZH 2mm yellow


Halogen-free and flame-retardant sheath according to IEC-60754-2, IEC-60332-1 and IEC-61034  
 EFB fiber optic connectors meet the minimum quality class Grade B/2 according to IEC-61753-1 for singlemode and Grade A/1 for multimode according to IEC 61753-122-2 (UPC cut)  
 100% tested and with individual measurement report

### Tekniske egenskaber

### Available variants

| ArtNr.    | Bezeichnung                                                    | Length | Length tolerance |
|-----------|----------------------------------------------------------------|--------|------------------|
| 00381.1   | Duplex Patchcable LC/APC-LC/APC OS2 G652D 1m LSZH 2mm yellow   | 1.0 m  | ±5 %             |
| 00381.2   | Duplex Patchcable LC/APC-LC/APC OS2 G652D 2m LSZH 2mm yellow   | 2.0 m  | ±5 %             |
| 00381.3   | Duplex Patchcable LC/APC-LC/APC OS2 G652D 3m LSZH 2mm yellow   | 3.0 m  | ±5 %             |
| 00381.5   | Duplex Patchcable LC/APC-LC/APC OS2 G652D 5m LSZH 2mm yellow   | 5.0 m  | ±5 %             |
| 00381.7,5 | Duplex Patchcable LC/APC-LC/APC OS2 G652D 7,5m LSZH 2mm yellow | 7.5 m  | ±5 %             |
| 00381.10  | Duplex Patchcable LC/APC-LC/APC OS2 G652D 10m LSZH 2mm yellow  | 10.0 m | ±5 %             |
| 00381.15  | Duplex Patchcable LC/APC-LC/APC OS2 G652D 15m LSZH 2mm yellow  | 15.0 m | ±5 %             |
| 00381.20  | Duplex Patchcable LC/APC-LC/APC OS2 G652D 20m LSZH 2mm yellow  | 20.0 m | ±5 %             |
| 00381.0,5 |                                                                | 0.5 m  |                  |
| 00381.25  |                                                                | 25.0 m |                  |
| 00381.30  |                                                                | 30.0 m |                  |
| 00381.35  |                                                                | 35.0 m |                  |
| 00381.40  |                                                                | 40.0 m |                  |
| 00381.50  |                                                                | 50.0 m |                  |

### datasheets.content.drawings



### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.