


DATASHEET

Duplex Patchcable E2000®/APC-LC OS2 G657A1 25m 3mm yellow



General data

Fiber jumper are well defined components in international standard of structured cabling ISO/IEC11801. Due to many different network protocols created in the last 25 years , also a wide range of connectors had been developed. Some of them are still important today: LC, SC, E2000®, MPO/MTP.

Fiber jumper (patchcord) are defined as shortest connection between passive interface and active deviceport, regarding structured cabling standard. Rating of performance, known as category, as well as performance of total transmission channel, known as link class, Similar descriptions for patchcords: Connection cable, drop cable, adapter cable, interconnecting cord, Jumper

Features of EFB fiber optic patch cables

Tension relief reinforced with aramid yarn

Halogen-free and flame-retardant sheath according to IEC-60754-2, IEC-60332-1 and IEC-61034

Tekniske egenskaber

Available variants


This datasheet was created automatically on 06-10-2026 . Technical changes reserved.

DATASHEET

Duplex Patchcable E2000®/APC-LC OS2 G657A1 25m 3mm yellow

ArtNr.	Bezeichnung	Length	Outer diameter sheath single fibre	Length tolerance
00937.0,5	Duplex Patchcable E2000®/APC-LC OS2 G657A1 0,5m 3mm yellow	0.5 m	3.0 mm	±5 %
00937.1	Duplex Patchcable E2000®/APC-LC OS2 G657A1 1m 3mm yellow	1.0 m	3.0 mm	±5 %
00937.2	Duplex Patchcable E2000®/APC-LC OS2 G657A1 2m 3mm yellow	2.0 m	3.0 mm	±5 %
00937.3	Duplex Patchcable E2000®/APC-LC OS2 G657A1 3m 3mm yellow	3.0 m	3.0 mm	±5 %
00937.5	Duplex Patchcable E2000®/APC-LC OS2 G657A1 5m 3mm yellow	5.0 m	3.0 mm	±5 %
00937.7,5	Duplex Patchcable E2000®/APC-LC OS2 G657A1 7,5m 3mm yellow	7.5 m	3.0 mm	±5 %
00937.10	Duplex Patchcable E2000®/APC-LC OS2 G657A1 10m 3mm yellow	10.0 m	3.0 mm	±5 %
00937.15	Duplex Patchcable E2000®/APC-LC OS2 G657A1 15m 3mm yellow	15.0 m	3.0 mm	±5 %
00937.20	Duplex Patchcable E2000®/APC-LC OS2 G657A1 20m 3mm yellow	20.0 m	3.0 mm	±5 %
00937.25	Duplex Patchcable E2000®/APC-LC OS2 G657A1 25m 3mm yellow	25.0 m	3.0 mm	±5 %
00937.30	Duplex Patchcable E2000®/APC-LC OS2 G657A1 30m 3mm yellow	30.0 m	3.0 mm	±5 %
00937.35		35.0 m	3.0 mm	
00937.40		40.0 m	3.0 mm	

datasheets.content.drawings



Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 06-10-2026 . Technical changes reserved.