
# DATASHEET







## General data

Fiber jumper are well defined components in international standard of structured cabling ISO/IEC11801.
Due to many different network protocols created in the last 25 years , also a wide range of connectors had been developed. Some of them are still important today: LC, SC, E2000®, MPO/MTP.

Fiber jumper (patchcord) are defined as shortest connection between passive interface and active deviceport, regarding structured cabling standard. Rating of performance, known as category, as well as performance of total transmission channel, known as link class,Similar descriptions for patchcords: Connection cable, drop cable, adapter cable, interconnecting cord, Jumper

**Features of EFB fiber optic patch cables**
Tension relief reinforced with aramid yarn
Halogen-free and flame-retardant sheath according to IEC-60754-2, IEC-60332-1 and IEC-61034
EFB fiber optic connectors meet the minimum quality class Grade B/2 according to IEC-61753-1 for singlemode and Grade A/1 for multimode according to IEC 61753-122-2 (UPC cut)
100% tested and with individual measurement report

## Tekniske egenskaber

## Available variants

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50


info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

| ArtNr. | Bezeichnung | Length | Length tolerance |
|---|---|---|---|
| O0948.0,5 | Simplex patch cable LC-LC OS2 G657A2 0.5m LSZH 2mm yellow | 0.5 m | ±5 % |
| O0948.1 | Simplex patch cable LC-LC OS2 G657A2 1m LSZH 2mm yellow | 1.0 m | ±5 % |
| O0948.2 | Simplex patch cable LC-LC OS2 G657A2 2m LSZH 2mm yellow | 2.0 m | ±5 % |
| O0948.3 | Simplex patch cable LC-LC OS2 G657A2 3m LSZH 2mm yellow | 3.0 m | ±5 % |
| O0948.5 | Simplex patch cable LC-LC OS2 G657A2 5m LSZH 2mm yellow | 5.0 m | ±5 % |
| O0948.7,5 | Simplex patch cable LC-LC OS2 G657A2 7.5m LSZH 2mm yellow | 7.5 m | ±5 % |
| O0948.10 | Simplex patch cable LC-LC OS2 G657A2 10m LSZH 2mm yellow | 10.0 m | ±5 % |
| O0948.15 | Simplex patch cable LC-LC OS2 G657A2 15m LSZH 2mm yellow | 15.0 m | ±5 % |
| O0948.20 | | 20.0 m | |
| O0948.25 | | 25.0 m | |
| O0948.30 | | 30.0 m | |
| O0948.40 | | 40.0 m | |
| O0948.50 | | 50.0 m | |

## datasheets.content.drawings




**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION