DATASHEET



General data

Characteristics and advantages of Trunk cables:
- 2 up to 48 fibers per cable (CPR class B2ca)
- Pre-assembled, polished and factory-tested
- Both-sided assembled with stepped plug whips
- Ready to use, no need for expensive splice- and measuring equipment
- With Premium or Standard cable divider at customers choice
- Attenuation protocol for each assembled connector included in delivery
- All possible combinations of connectors like LC and SC
- Identification with cable markers
- Delivery depending on length and type: one way drum or cable ring

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Cable type connector connection 2	Length	Number of connectors connection 1	Number of connectors connection 2	Number of fibres
O8122.1-B2		Universal cable	1.0 m	4	4	4
O8132.1-B2		Universal cable	1.0 m	8	8	8
O8814.1-B2		Universal cable	1.0 m	12	12	12

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION