


DATASHEET

Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,120m Dca LSZH



General data

EFB sets standards in high quality

For many years, EFB has been offering individual fiber optic assemblies from its own production for insertion into cable ducts and shafts. Now there is also a standard line, which is kept in stock. These are pre-assembled trunk cables with SC connectors in the OS2, OM3 and OM4 categories. The stocked lengths can be found in the overview below.

Advantages:

Fast delivery: standard lengths up to 200 m in standard quantities available from stock

Reduction of installation costs: No splicing and assembly equipment required

Reduced installation time: cable ready for direct installation

Traceable quality: cable with serial number and measurement protocol

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.

DATASHEET

Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,120m Dca LSZH

Performance features:

4, 8 or 12 fibers per cable

Fibre class OS2, OM3 or OM4

Factory production, polishing and function test

Double-sided assembled stepped cable whips (longest length 1 m)

Identification of the remote individual cables with cable markers (numbers)

Serial number on the cable

Attenuation protocol for each individual fiber is provided

Delivery on both sides with fabric hose as drawing-in tube

Delivery up to 40 m in polybag, from 50 m on disposable drum

Raw cable: CPR-Class Dca

Length of the draw-in tube of 130cm, diameter: 4 fiber approx. 10mm, 8 fiber approx. 15mm, 12 fiber approx. 20mm

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Length	Outer diameter sheath single fibre	Length tolerance
08301S100S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,10m Dca LSZH	10 m	2 mm	±5 %
08301S200S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,20m Dca LSZH	20 m	2 mm	±5 %
08301S700S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,70m Dca LSZH	70 m	2 mm	±5 %
08301S900S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,90m Dca LSZH	90 m	2 mm	±5 %
08301S1200S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,120m Dca LSZH	120 m	2 mm	±5 %
08301S1400S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,140m Dca LSZH	140 m	2 mm	±5 %
08301S1500S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,150m Dca LSZH	150 m	2 mm	±5 %
08301S1600S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,160m Dca LSZH	160 m	2 mm	±5 %
08301S1700S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,170m Dca LSZH	170 m	2 mm	±5 %
08301S1800S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,180m Dca LSZH	180 m	2 mm	±5 %
08301S1900S2	Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,190m Dca LSZH	190 m	2 mm	±5 %

Note on Intended Use

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.



DATASHEET

Trunk cable U-DQ(ZN)BH OS2 4E (1x4) SC-SC,120m Dca LSZH

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.

