


DATASHEET

Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,110m Dca LSZH



General data

EFB sets standards in high quality

For many years, EFB has been offering individual fiber optic assemblies from its own production for insertion into cable ducts and shafts. Now there is also a standard line, which is kept in stock. These are pre-assembled trunk cables with LC connectors in the OS2, OM3 and OM4 categories. The stocked lengths can be found in the overview below.

Advantages:

Fast delivery: standard lengths up to 200 m in standard quantities available from stock

Reduction of installation costs: No splicing and assembly equipment required

Reduced installation time: cable ready for direct installation

Traceable quality: cable with serial number and measurement protocol

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,110m Dca LSZH

Performance features:

4, 8 or 12 fibers per cable

Fibre class OS2, OM3 or OM4

Factory production, polishing and function test

Double-sided assembled stepped cable whips (longest length 1 m)

Identification of the remote individual cables with cable markers (numbers)

Serial number on the cable

Attenuation protocol for each individual fiber is provided

Delivery on both sides with fabric hose as drawing-in tube

Delivery up to 40 m in polybag, from 50 m on disposable drum

Raw cable: CPR-Class Dca

Length of the draw-in tube of 130cm, diameter: 4 fiber approx. 10mm, 8 fiber approx. 15mm, 12 fiber approx. 20mm

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Length	Outer diameter sheath single fibre	Length tolerance
08303S100M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,10m Dca LSZH	10 m	2 mm	±5 %
08303S200M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,20m Dca LSZH	20 m	2 mm	±5 %
08303S300M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,30m Dca LSZH	30 m	2 mm	±5 %
08303S400M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,40m Dca LSZH	40 m	2 mm	±5 %
08303S500M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,50m Dca LSZH	50 m	2 mm	±5 %
08303S600M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,60m Dca LSZH	60 m	2 mm	±5 %
08303S700M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,70m Dca LSZH	70 m	2 mm	±5 %
08303S800M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,80m Dca LSZH	80 m	2 mm	±5 %
08303S900M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,90m Dca LSZH	90 m	2 mm	±5 %
08303S1000M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,100m Dca LSZH	100 m	2 mm	±5 %
08303S1100M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,110m Dca LSZH	110 m	2 mm	±5 %

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,110m Dca LSZH

O8303S1200M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,120m Dca LSZH	120 m	2 mm	±5 %
O8303S1300M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,130m Dca LSZH	130 m	2 mm	±5 %
O8303S1400M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,140m Dca LSZH	140 m	2 mm	±5 %
O8303S1500M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,150m Dca LSZH	150 m	2 mm	±5 %
O8303S1600M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,160m Dca LSZH	160 m	2 mm	±5 %
O8303S1700M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,170m Dca LSZH	170 m	2 mm	±5 %
O8303S1800M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,180m Dca LSZH	180 m	2 mm	±5 %
O8303S1900M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,190m Dca LSZH	190 m	2 mm	±5 %
O8303S2000M3	Trunk cable U-DQ(ZN)BH OM3 4G (1x4) LC-LC,200m Dca LSZH	200 m	2 mm	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

