
# DATASHEET

## Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,70m Dca LSZH



### General data

**EFB sets standards in high quality**

For many years, EFB has been offering individual fiber optic assemblies from its own production for insertion into cable ducts and shafts. Now there is also a standard line, which is kept in stock. These are pre-assembled trunk cables with LC connectors in the OS2, OM3 and OM4 categories. The stocked lengths can be found in the overview below.

**Advantages:**
**Fast delivery:** standard lengths up to 200 m in standard quantities available from stock
**Reduction of installation costs:** No splicing and assembly equipment required
**Reduced installation time:** cable ready for direct installation
**Traceable quality:** cable with serial number and measurement protocol

**This datasheet was created automatically on 30-10-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,70m Dca LSZH

**Performance features:**
4, 8 or 12 fibers per cable
Fibre class OS2, OM3 or OM4
Factory production, polishing and function test
Double-sided assembled stepped cable whips (longest length 1 m)
Identification of the remote individual cables with cable markers (numbers)
Serial number on the cable
Attenuation protocol for each individual fiber is provided
Delivery on both sides with fabric hose as drawing-in tube
Delivery up to 40 m in polybag, from 50 m on disposable drum
Raw cable: CPR-Class Dca
Length of the draw-in tube of 130cm, diameter: 4 fiber approx. 10mm, 8 fiber approx. 15mm, 12 fiber approx. 20mm

### Tekniske egenskaber

### Available variants

| ArtNr. | Bezeichnung | Length | Outer diameter sheath single fibre | Length tolerance |
|---|---|---|---|---|
| O8322S10OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,10m Dca LSZH | 10 m | 2 mm | ±5 % |
| O8322S20OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,20m Dca LSZH | 20 m | 2 mm | ±5 % |
| O8322S30OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,30m Dca LSZH | 30 m | 2 mm | ±5 % |
| O8322S40OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,40m Dca LSZH | 40 m | 2 mm | ±5 % |
| O8322S50OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,50m Dca LSZH | 50 m | 2 mm | ±5 % |
| O8322S60OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,60m Dca LSZH | 60 m | 2 mm | ±5 % |
| O8322S70OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,70m Dca LSZH | 70 m | 2 mm | ±5 % |
| O8322S80OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,80m Dca LSZH | 80 m | 2 mm | ±5 % |
| O8322S90OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,90m Dca LSZH | 90 m | 2 mm | ±5 % |
| O8322S100OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,100m Dca LSZH | 100 m | 2 mm | ±5 % |
| O8322S110OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,110m Dca LSZH | 110 m | 2 mm | ±5 % |
| O8322S120OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,120m Dca LSZH | 120 m | 2 mm | ±5 % |
| O8322S130OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,130m Dca LSZH | 130 m | 2 mm | ±5 % |
| O8322S140OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,140m Dca LSZH | 140 m | 2 mm | ±5 % |
| O8322S150OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,150m Dca LSZH | 150 m | 2 mm | ±5 % |

**This datasheet was created automatically on 30-10-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,70m Dca LSZH

| | | | | |
|---|---|---|---|---|
| O8322S160OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,160m Dca LSZH | 160 m | 2 mm | ±5 % |
| O8322S170OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,170m Dca LSZH | 170 m | 2 mm | ±5 % |
| O8322S180OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,180m Dca LSZH | 180 m | 2 mm | ±5 % |
| O8322S190OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,190m Dca LSZH | 190 m | 2 mm | ±5 % |
| O8322S200OS2 | Trunk cable U-DQ(ZN)BH OS2 8E (1x8) LC-LC,200m Dca LSZH | 200 m | 2 mm | ±5 % |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

**This datasheet was created automatically on 30-10-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION